

## PRODUCT PROFILES



## PRODUCT SPECIFICATIONS

	Roofglory VILLA TILE	Roofglory TILE	RoofglorySHINGLE XD®	SHAKE XD®	SHAKE
<b>Min Roof Pitch ▶</b>	3:12	3:12	4:12	3:12	3:12
<b>Panel Size ▶</b>	17" x 44-1/4"	16-1/2" x 52"	14-1/8" x 52-3/8"	14-1/8" x 52-1/8"	14-5/8" x 53"
<b>Installed Exposure ▶</b>	14-1/2" x 39-1/2"	14-1/2" x 50"	12-1/4" x 49-1/2"	12-3/8" x 49-7/8"	12-5/8" x 51"
<b>Panels per Square ▶</b>	25.2	20	23.8	23.4	22.4
<b>Installed Weight ▶</b>	160 lbs. / sq.	150 lbs. / sq.	150 lbs. / sq.	150 lbs. / sq.	150 lbs. / sq.

## AVAILABLE COLORS (Final color selection should be made from an actual product sample)

<b>Roofglory VILLA TILE</b>									
<b>Roofglory TILE</b>									
<b>Roofglory SHINGLE XD</b>									
<b>Roofglory SHAKE XD</b>									
<b>Roofglory shake</b>									

## Roofglory METAL ROOFING COOL ROOF COLORS

Available on all RoofgloryMetal Roofing profiles:



\*Please note these colors are MTO (made to order) and production times may be extended.



Cool colors meet California Title 24 Cool Roof requirements.

## WARRANTY/COMPOSITION

### Warranties

- Lifetime Limited Warranty\*
- 120 mph Wind Speed Warranty
- Hail Stone Penetration Warranty

### Composition

- Steel – Aluminum-Zinc Hot Dip Coating
- Acrylic Priming System
- Acrylic Basecoat
- Ceramic Coated Stone Granules
- Acrylic Over-Glaze

\*DECRA offers a Lifetime Limited Warranty on single family residential in the U.S. & Canada.

### Miami - Dade County, Florida

- Miami Dade County NOA#18-1015.06 Tile, Villa Tile, Shake, Shingle Plus, Shake XD
- Miami Dade County NOA#17-1227.02 DECRA Ridge Vent

### Florida Building Code

- Approval #9759-R9: Shake, Tile, Shingle XD, Shake XD, Villa Tile, Shingle Plus
- D30800.12.09-R7 for FL9759-R9
- RoofgloryRidge Vent: FL17492-R3 II NOA 17122702 2017

### Texas Department of Insurance

- Products Qualifying for Impact Resistant Roofing Credits
- Roofing Installation Information and Certification for Reduction in Residential Insurance Premiums
- TDI Report #RC-282 Wind Resistance – Villa Tile
- TDI Report #RC-235 Wind Resistance – Shake XD
- TDI Report #RC-281 Wind Resistance – Tile, Shake, Shingle Plus
- TDI Report #RC-548 Wind Resistance - Shingle XD

### National Building Code of Canada

- CCMC Evaluation Report #13551-R (direct-to-deck)
- CCMC Evaluation Report #10241-R (on battens)

### Underwriters Laboratories, Inc – Listings File #R14710

- Fire – UL 790 (ASTM E108 – A, B & C)
- Fire – UL CAN/ULC-S107 (Canada)
- Hail – UL 2218 (Class 4)
- Uplift – UL 580 & UL 1897 – Class 90

### Additional Testing for LEED® and CA Title 24 Cool Colors

- ASTM – E903 Solar Absorptance, Reflectance, and Transmittance of Materials Using Integrating Spheres

- ASTM – E408 Total Normal Emittance of Surfaces Using Inspection-Meter Techniques
- ASTM – E1980 Calculating Solar Reflectance Index of Horizontal and Low-Sloped Opaque Surfaces

### ISO Management System Compliance

- ISO 9001:2015 Quality Management System
- ISO 14001:2015 Environmental Management System
- ISO 45001:2018 Occupational Health & Safety Management System

## Roofglory Products Meet Requirements For

### International Code Council (IRC, IBC Codes)

INCLUDES: City of Los Angeles (LARC, LABC)  
California State (CRC, CBC)

- ESR-2901 – Tile, Shake, Shingle Plus (battens)
- ESR-1754 – Villa Tile, Shake XD, Shingle XD, Shingle Plus (direct to deck)

